


ENDCAP



FLEXIBILITY

MERIAL	HIGHT				LOW
MIT108				MIT107	MIT106
MIT108S				MIT107BX	MIT106S
MIT108SR	(ZINC PROTECH)				
MIT108HT	(HIGHT TEMP)				



COLORS NORMAL COLOR-----BLACK=B, BLUE=BL, YELLOW=Y, GREEN=G, RED=R
 SPECIAL COLOR-----CLEAR=C, PINK CLEAR= P-C, BLUE CLEAR=B-C, YELLOW CLEAR=Y-C

ød (MM)	L (STD.)	T (General)	Color	ød (MM)	L (STD.)	T (General)	Color	ød (MM)	L (STD.)	T (General)	Color
±0.2	±1.5	±0.3		±0.2	±1.5	±0.3		±0.2	±1.5	±0.3	
1.70	15.0	0.8	C	7.50	30.0	1.2	B	12.50	20.0	1.3	B
3.00	20.0	1.0	C	7.50	8.0	1.0	B	13.00	15.0	1.0	B
3.00	8.0	0.8	B	7.50	30.0	1.3	B	13.50	15.0	1.0	C-NS
3.80	22.0	0.8	C	7.50	20.0	1.0	C	13.50	25.0	1.0	O
3.80	29.0	0.8	C	8.00	30.0	0.8	Y	14.00	20.0	1.2	Y
3.80	1.5	1.0	C	8.00	20.0	1.0	Y	14.50	20.0	1.5	LB
3.80	20.0	0.8	W	8.20	39.0	1.0	BL-C	15.00	20.0	1.2	B
4.00	19.0	1.0	C	8.50	30.0	1.2	C	15.00	20.0	1.0	C
4.00	29.0	1.0	C	8.50	15.0	1.0	C	15.50	30.0	1.0	B
4.00	19.0	0.8	C	8.50	15.0	0.8	R	15.50	62.0	1.0	R
4.00	10.0	1.0	Y	8.50	20.0	1.3	BL	15.50	25.0	1.6	B
4.50	17.0	1.0	V-C	8.60	45.5	1.0	Y-C	16.00	25.0	1.6	B
4.50	22.0	1.0	G-C	9.00	20.0	1.3	W,BL	16.00	20.0	1.2	Y
4.50	30.0	1.0	C	9.00	30.0	0.8	G	16.50	30.0	1.2	Y
4.50	20.0	0.8	B	9.00	15.0	0.8	OR	17.00	33.0	1.0	Y
4.50	9.0	0.3	G-C	9.50	20.0	1.2	B	18.00	71.0	1.0	B
4.50	30.0	2.0	B-C	9.50	25.0	1.5	Y	18.00	25.0	1.6	O
5.00	17.0	1.0	P-C	9.50	45.0	1.5	Y	18.00	20.0	1.2	Y
5.00	22.0	1.0	C	9.50	30.0	1.3	BR	18.50	20.0	1.0	C
6.00	15.0	1.0	Y-C	10.00	20.0	1.0	Y	22.00	20.0	1.2	Y
6.00	25.0	1.0	B	10.50	20.0	1.3	Y	22.20	20.0	1.0	C
6.00	20.0	1.0	W	10.50	25.0	1.2	B	24.00	15.0	1.5	B
6.00	15.0	0.8	B	10.50	20.0	1.0	B	25.00	20.0	1.2	B
6.50	30.0	1.2	Y	11.50	35.0	1.3	OR	27.00	26.0	1.2	C
6.50	20.0	1.0	C	11.50	30.0	0.8	W	30.00	33.0	1.0	G
6.80	20.0	0.8	B	12.00	20.0	1.2	B	30.00	20.0	1.2	Y
7.00	25.0	1.0	B	12.00	20.0	2.0	B	35.00	20.0	1.2	Y
7.00	20.0	1.0	BL	12.00	30.0	0.8	BL	60.00	30.0	1.0	B
7.00	15.0	1.0	R	12.00	20.0	1.2	Y	87.00	45.0	2.0	B
7.00	20.0	1.0	C	12.00	38.0	1.0	BL				

Others Size without in This table .Pls contact **02-0108580**

